



VERTICALLY POLARISED PANEL ANTENNA GSM900 VP/60/14/0 Type 1706

- ❑ 60 DEGREE SECTOR
- ❑ SUPPRESSED SIDELOBES

Vertically polarised panel antennas from Racal have been designed to provide high RF performance, with highly suppressed sidelobes to minimise interference with adjacent cells.

A number of models provide variations in both gain and downtilt to exactly suit the required cell coverage. Superior design coupled with advanced manufacturing techniques guarantee consistent product quality & performance.

TECHNICAL SPECIFICATION

Frequency	870-960 MHz
Gain	14 dBi
VSWR	1.3:1 max
Horizontal Beamwidth	60°
Vertical Beamwidth	11.5°
Fixed Electrical Downtilt	0°
Upper Sidelobe Suppression	>18dB
Front-to-Back Ratio	>25dB
Power Rating	400W
Connectors	7/16" DIN female bulkhead
Impedance	50Ω
Dimensions (LxWxD)	1850 x 300 x 145 mm
Temperature Range	-30°C to +50°C
Wind Loading	776N @ 45m/s
Operational Wind Speed	45 m/s
Survival Wind Speed	56 m/s
Lightning Protection	DC grounded
Weight	13.3kg
Bracket Size	To suit pole 48-115mm
Bracket Downtilt	+6 to -6°

