



**DUAL BAND OMNIDIRECTIONAL
MICROCELL ANTENNA
GSM900/1800 VP/360/2
TYPE: 2141**

- ❑ **IN-BUILDING APPLICATIONS**
- ❑ **COMPACT LOW PROFILE**

The '3G Series' of antennas have been designed to easily facilitate the installation of Third Generation cellular infrastructure into new or existing networks.

The compact 2141 model provides an attractively styled unit for in-building or microcell applications.



TECHNICAL SPECIFICATION

	GSM900	GSM1800
Frequency Range	870-960	1710-1880MHz
Gain	2dBi	
VSWR	1:65:1	
Horizontal Beamwidth	Omnidirectional (360°)	
Vertical Beamwidth	95° to 100° to -3dB points	
Power Rating	50W	
Connector	N female	
Impedance	50Ω	
Dimensions (LxWxD)	210 x 80 x 90 mm	
Weight	0.35kg	

INOTEK ANTENNAS LTD

54, Ashdown Road, Chandler's Ford, Eastleigh, Hampshire, SO53 5QJ United Kingdom

Tel: +44 (0) 2380 254289, Fax: +44 (0) 191 3920133, email: sales@inotekantennas.com, www.inotekantennas.com

Inotek Antennas reserve the right to vary in detail from the description and specification in this publication. Issue: 04/07