



DUAL POLARISED ANTENNA UMTS XP/85/6/0 TYPE: 2144

- ❑ **IN-BUILDING 3G APPLICATIONS**
- ❑ **COMPACT LOW PROFILE**


The '3G Series' of antennas have been designed to easily facilitate the installation of Third Generation cellular infrastructure into new or existing networks.

The compact 2144 model provides an attractively styled unit for microcell applications.



TECHNICAL SPECIFICATION

Frequency Range	1900-2170MHz
Gain	6dBi
VSWR	1:4.1
Polarisation	+45° and -45°
Horizontal Beamwidth	87°
Vertical Beamwidth	86°
Fixed Electrical Downtilt	0°
Isolation Between Ports	30dB
Power Rating	60W
Impedance	50Ω
Lightning Protection	DC grounded
Connectors	N type female
Dimensions (LxWxD)	230 x 188 x 80 mm
Weight	0.8kg
Bracket	Wall mounting



INOTEK ANTENNAS LTD

54, Ashdown Road, Chandler's Ford, Eastleigh, Hampshire, SO53 5QJ United Kingdom

Tel: +44 (0) 2380 254289, Fax: +44 (0) 191 3920133, email: sales@inotekantennas.com, www.inotekantennas.com

Inotek Antennas reserve the right to vary in detail from the description and specification in this publication. Issue: 04/07