




## DUAL-BAND, DUAL POLARISED ANTENNA GSM900/1800 XP/80/6/0 TYPE 2145

### □ INBUILT DIPLEXER


This compact dual-band, dual-polar unit is intended for Microcell applications, either indoor or outdoor, where visual impact is important. It is fitted with inbuilt diplexers for each port to simplify connection. Sidelobe suppression reduces the possibility of interference from adjacent cells. Wall mounting is easily carried out using the attached joggle plates.

### TECHNICAL SPECIFICATION

	GSM900	GSM1800
Frequency	870-960Mhz	1710-1880Mhz
Gain	6dBi	6dBi
VSWR	1.6:1 max	1.6:1 max
Horizontal Beamwidth	80°	83°
Vertical Beamwidth	80°	74°
Polarisation	+45° and -45°	+45° and -45°
Fixed Electrical Downtilt	0°	0°
Front-to-Back Ratio	>17dB	>16dB
Isolation Between Ports	>-20dB	>-25dB
Isolation Between Bands	30dB	30dB
Power Rating	30W	30W
Connectors (bottom)	N type female x 2	-
Impedance	50Ω	-
Dimensions (LxWxD)	350 x 217 x 56 mm	-
Wind Loading	115N @ 45m/s	-
Operational Wind Speed	45m/s	-
Survival Wind Speed	56m/s	-
Weight	1.5kg	-
Temperature	-55° to +70°C	-
Mounting	Wall Mounting	-



GSM900



GSM1800

INOTEK ANTENNAS LTD

54, Ashdown Road, Chandler's Ford, Eastleigh, Hampshire, SO53 5QJ United Kingdom

Tel: +44 (0) 2380 254289, Fax: +44 (0) 191 3920133, email: sales@inotekantennas.com, www.inotekantennas.com

Inotek Antennas reserve the right to vary in detail from the description and specification in this publication. Issue: 04/07